



The Right Connection™

Dixon "Bayco" Relief Valve Minimum and Maximum Settings

19-Oct-09

Pressure and Vacuum relief valves can be factory ordered with a relief setting from within the tables below.

Pressure Relief Valves, Min & Max Setting

Valve Series	Factory Setting	
	Minimum	Max Setting
2180	2 PSI	25 PSI
A2180	2 PSI	27 PSI
A2180ADJ*	9 PSI*	30 PSI*
2182	3 PSI	24 PSI
A2182	6 PSI	27 PSI
2215*	12 PSI*	30 PSI*
3180	4 PSI	30 PSI
A3180	6 PSI	32 PSI
A3180ADJ*	9 PSI*	30 PSI*

*** 2215, A2180ADJ and A3180ADJ notes:**

Valves marked with an Astrix (*) are customer adjustable by a further +/- 3 PSI.

(Settings below 9 PSI are obtainable by turning the valve adjustment screw. Example for an 8 PSI setting the valve adjustment would be +4/-2, for 7 PSI +5/-1 and for 6 PSI +6/-0)

(Settings above 30 PSI are obtainable by turning the valve adjustment screw. Example for an 31 PSI setting the valve adjustment would be +2/-4, for 32 PSI +1/-5 and for 33 PSI +0/-6)

Vacuum Relief Valves, Min & Max Setting

Valve Series	Factory Setting	
	Minimum	Max Setting
1120	6" Hg	24" Hg
2120	5" Hg	24" Hg
3120	11" Hg	25" Hg