LFAR PVC Red Layflat Heavy Duty



Designed for heavy-duty applications for the transfer of water and other non-corrosive liquids on building sites, in mining applications and for general civil, construction, irrigation and drainage operations.



Hose Construction

Tube: PVC - red PVC - red PVC - red Polyester yarn

Features

- Abrasion resistant
- Ozone resistant
- · Weather resistant
- Extruded

Temperature

• -10°C to 60°C

Standards

Nil

Part Number

• To view available part number options please click here

Dimensions (mm)		Pressures						Bend	
		Working		Burst		Vacuum (bar)	Weight (kg/mtr)	Radius	Coil
ID	OD	PSI	Bar	PSI	Bar	(Dai)	(kg/IIII)	(mm)	Lengths
IO)(€ W		(mtr)
38.1	42.1	150	10	450	30	n/a	0.30	n/a	100
50.8	54.8	150	10	450	30	n/a	0.42	n/a	100
63.5	67.5	150	10	450	30	n/a	0.55	n/a	100
76.2	80.2	125	9	375	26	n/a	0.66	n/a	100
101.6	106.6	125	9	375	26	n/a	1.00	n/a	100
152.4	157.8	102	7	306	21	n/a	1.65	n/a	100
203.2	210.2	73	5	219	15	n/a	2.20	n/a	100

Product Code: DA33