DATA SHEET

# H020 TPR/Food Grade Delivery Hose

The Right Connection®

Manufactured from high-quality PVC, boasting outstanding flexibility, featuring a glass-clear translucent appearance with a hint of blue, ensuring excellent visibility of transferred products. This versatile hose is perfectly suited for a wide range of applications, including the transfer of air, water, food and beverage items, as well as petroleum products. It finds utility across various industries such as food production, mining, construction, general industrial and agricultural sectors. Not suitable as a permanent fuel line.

**Hose Construction**

**Tube:** PVC - transparent
**Cover:** PVC smooth - transparent
**Reinforcing:** Polyester yarn, red spiral tracer

**Special Features**

- UV stabilised
- Abrasion resistant
- Oil mist resistant
- Extruded

**Temperature**

- -5°C to 60°C

**Standards**

- AS/NZS 2554 Class B

**Part Number**

- To view available part number options please click here

| Dimensions (mm) | | Pressures | | | | Vacuum (bar) | Bend Radius (mm) | Weight (kg/mtr) | Coil Lengths (mtr) |
|---|---|---|---|---|---|---|---|---|---|
| | | Working | | Burst | | | | | |
| ID | OD | PSI | Bar | PSI | Bar | | | | |
| 6.4 | 12.0 | 232 | 16 | 928 | 64 | n/a | 75 | 0.12 | 20, 100 |
| 7.9 | 14.0 | 232 | 16 | 928 | 64 | n/a | 95 | 0.16 | 20, 100 |
| 9.5 | 16.0 | 232 | 16 | 928 | 64 | n/a | 120 | 0.18 | 20, 100 |
| 12.7 | 19.0 | 232 | 16 | 928 | 64 | n/a | 150 | 0.22 | 20, 100 |
| 15.9 | 24.0 | 232 | 16 | 928 | 64 | n/a | 180 | 0.32 | 20, 100 |
| 19.1 | 28.0 | 232 | 16 | 928 | 64 | n/a | 240 | 0.47 | 20, 100 |
| 25.4 | 35.0 | 232 | 16 | 928 | 64 | n/a | 300 | 0.65 | 20, 100 |
| 31.8 | 43.0 | 150 | 10 | 600 | 40 | n/a | 385 | 0.88 | 20, 100 |
| 38.1 | 50.5 | 150 | 10 | 600 | 40 | n/a | 480 | 1.12 | 20, 100 |
| 50.8 | 63.5 | 150 | 10 | 600 | 40 | n/a | 600 | 1.60 | 20, 100 |

Product Code: DA01

customerservice@dixonvalve.com.au . 1300 134 651