

Big Mouth™ Diesel Nozzle



Application:	Roto-matic latch pin provides positive auto shut-off.
Design:	Micro-touch valve allows precise flow control. Pure PTFE packing eliminates stem leaks. Super tough nylon hold-open clip & hand guard bend, but won't break. Snap-on handle cover makes changing scuff guards easy
Colour:	Yellow scuff guard

Inlet Size (inch)	Spout Size (inch)	Weight (kg)	Approx Flow Rate @ 20 PSI (GPM)	Part No.	Price \$
Non Underwriters Listed nozzle					
with trigger hold-open clip					
1 NPT	1 1/8	1.4	20	DFN100	321.07
Underwriters Listed nozzle					
with trigger hold-open clip with 'no pressure, no flow' safety valve					
1 NPT	1 1/8	1.7	20	DFN100-NPNF	426.70
without trigger hold-open clip					
1 NPT	1 1/8	1.7	20	DFN100-NC	350.90

Price Group: BY
AS02

Farm & Consumer Nozzles

Application:	Automatic fuel nozzles designed for use with small 12 volt & AC utility pumps as well as large farm & consumer pumps
Design:	Heavy duty, stronger & more secure hook makes it easy to hang the nozzle on the pump.
Colour:	Black scuff guard on gasoline nozzle, green scuff guard on diesel nozzle



Gasoline Nozzle



Diesel Nozzle

Inlet Size (inch)	Spout Size (inch)	Weight (kg)	Approx Flow Rate @ 20 PSI (GPM)	Part No.	Price \$
Non Underwriters Listed nozzle					
with trigger hold-open clip					
3/4 NPT	1 3/16	1.1	18	DN7UOBF	189.74
3/4 NPT	1 5/16	1.1	23	DN7LOBF	190.05
1 NPT	1 1/8	1.7	27	DFN100F ¹	379.30
with trigger hold-open clip with 'no pressure, no flow' safety valve					
3/4 NPT	1 3/16	1.1	18	DN7UOBF-NPNF	339.50
3/4 NPT	1 5/16	1.1	23	DN7LOBF-NPNF	339.50
1 NPT	1 1/8	1.7	27	DFN100F-NPNF	455.20
without trigger hold-open clip					
3/4 NPT	1 3/16	1.1	18	DN7UOBF-NC	263.60
3/4 NPT	1 5/16	1.1	23	DN7LOBF-NC	263.60
1 NPT	1 1/8	1.7	27	DFN100F-NC	379.30

¹ Hand-guard and rear back clip: super tough nylon

Price Group: BY
AS02

DEF Automatic Shutoff Nozzle (ADBLUE)

Q



Application:	Automatic shutoff nozzle designed for diesel exhaust fluid.
Features:	<ul style="list-style-type: none"> Aluminum body double coated inside and out with PTFE baked on at 500°F Stainless steel spout Maximum operating pressure: 50 PSI Wetted parts: stainless, acetal, PTFE FKM-A seals

Inlet Size (inch)	Spout Size (inch)	Weight (kg)	Approx Flow Rate @ 20 PSI (GPM)	Part No.	Price \$
3/4 BSPP	1 3/16	1.1	14	DEFN075	999.65

Price Group: BY
AS02



1300 134 651
dixonvalve.com.au

All prices exclude GST.
ADPL718