


**A**

## RigBoss™ Series - Drill Water - Brine (A220H)

|                      |   |
|----------------------|---|
| <b>Application:</b>  | Rugged but flexible hard wall hose designed for transfer of sea water, grey water and brine. Hose features 5,000kg end pull resistance. |
| <b>Tube:</b>         | Black IR/BR   |
| <b>Reinforcement</b> | High tensile textile cords with embedded steel wire and helix wire.   |
| <b>Cover:</b>        | Black CR; abrasion, ozone resistant   |
| <b>Temperature:</b>  | -20°C to 100°C  |
| <b>Lengths:</b>      | 20 mtr, 40 mtr and 61 mtr   |




| Hard Wall |                 |     |                      |     |        |                  |               |                  |                        |                |
|-----------|-----------------|-----|----------------------|-----|--------|------------------|---------------|------------------|------------------------|----------------|
| Part No.  | Dimensions (mm) |     | Working Pressure PSI | Bar | BP PSI | Bend Radius (mm) | Weight kg/mtr | Application      | End Pull Resistance kg | Price \$ per m |
|           | ID              | OD  |                      |     |        |                  |               |                  |                        |                |
| A220HW050 | 50              | 70  | 300                  | 20  | 1200   | 250              | 2.6           | Suction/Delivery | 5000                   | 228.66         |
| A220HW080 | 76              | 97  | 300                  | 20  | 1200   | 350              | 4.2           | Suction/Delivery | 5000                   | 302.04         |
| A220HW100 | 102             | 125 | 300                  | 20  | 1200   | 800              | 5.9           | Suction/Delivery | 5000                   | 421.15         |
| A220HW125 | 127             | 151 | 300                  | 20  | 1200   | 1000             | 8.3           | Suction/Delivery | 5000                   | 661.51         |

**Price Group: HR**  
DB46

## RigBoss™ Series - Drill Water - Brine (A220S)

|                      |   |
|----------------------|---|
| <b>Application:</b>  | Rugged but flexible soft wall hose designed for transfer of sea water, grey water and brine. Hose features 5,000kg end pull resistance. |
| <b>Tube:</b>         | Black IR/BR   |
| <b>Reinforcement</b> | High tensile textile cords  |
| <b>Cover:</b>        | Black CR; abrasion, ozone resistant   |
| <b>Temperature:</b>  | -20°C to 100°C  |
| <b>Lengths:</b>      | 20 mtr, 40 mtr and 61 mtr   |




| Soft Wall |                 |     |                      |     |        |                  |               |             |                        |                |
|-----------|-----------------|-----|----------------------|-----|--------|------------------|---------------|-------------|------------------------|----------------|
| Part No.  | Dimensions (mm) |     | Working Pressure PSI | Bar | BP PSI | Bend Radius (mm) | Weight kg/mtr | Application | End Pull Resistance kg | Price \$ per m |
|           | ID              | OD  |                      |     |        |                  |               |             |                        |                |
| A220SW050 | 50              | 68  | 300                  | 20  | 1200   | 400              | 3.0           | Delivery    | 5000                   | 182.92         |
| A220SW080 | 76              | 92  | 300                  | 20  | 1200   | 560              | 3.6           | Delivery    | 5000                   | 239.30         |
| A220SW100 | 102             | 122 | 300                  | 20  | 1200   | 800              | 5.2           | Delivery    | 5000                   | 371.17         |
| A220SW125 | 127             | 151 | 300                  | 20  | 1200   | 1000             | 7.3           | Delivery    | 5000                   | 606.20         |

**Price Group: HR**  
DB46

## RigBoss™ Series - Drill Water - Brine (A220FR)

|                      |   |
|----------------------|---|
| <b>Application:</b>  | Rugged but flexible hard wall hose designed for transfer of sea water, grey water and brine. Hose features 5,000kg end pull resistance and fire resistant cover in accordance with ISO 15441. |
| <b>Tube:</b>         | Black IR/BR   |
| <b>Reinforcement</b> | High tensile textile cords with embedded steel wire and helix wire.   |
| <b>Cover:</b>        | Black CR; abrasion, ozone resistant   |
| <b>Temperature:</b>  | -20°C to 100°C  |
| <b>Lengths:</b>      | 20 mtr, 40 mtr and 61 mtr   |



| Hard Wall Fire Resistant |                 |     |                      |     |        |                  |               |                  |                        |                |
|--------------------------|-----------------|-----|----------------------|-----|--------|------------------|---------------|------------------|------------------------|----------------|
| Part No.                 | Dimensions (mm) |     | Working Pressure PSI | Bar | BP PSI | Bend Radius (mm) | Weight kg/mtr | Application      | End Pull Resistance kg | Price \$ per m |
|                          | ID              | OD  |                      |     |        |                  |               |                  |                        |                |
| A220HW050FR              | 50              | 74  | 300                  | 20  | 1200   | 250              | 3.6           | Suction/Delivery | 5000                   | 280.13         |
| A220HW080FR              | 76              | 101 | 300                  | 20  | 1200   | 350              | 4.2           | Suction/Delivery | 5000                   | 369.49         |
| A220HW100FR              | 102             | 128 | 300                  | 20  | 1200   | 800              | 6.9           | Suction/Delivery | 5000                   | 517.28         |
| A220HW125FR              | 127             | 156 | 300                  | 20  | 1200   | 1000             | 8.3           | Suction/Delivery | 5000                   | 835.58         |

**Price Group: HR**  
DB46

Complete hose data specification sheets are available upon request.

