

A

## RigBoss™ Series - Dry Cement - Baryte (A820H)



Application:	Rugged but flexible hard wall hose featuring high abrasive resistant tube designed for transfer of dry cement and barytes. Hose features 5,000kg end pull resistance.
Tube:	Black SBR/NR blend, abrasion, ozone resistant, static conductive
Reinforcement	High tensile textile cords with embedded steel wire and helix wire.
Cover:	Black CR; abrasion, ozone resistant, static conductive
Temperature:	-20°C to 80°C
Lengths:	20 mtr, 40 mtr and 61 mtr

### Hard Wall

Part No.	Dimensions (mm)		Working Pressure PSI	Bar	BP PSI	Bend Radius (mm)	Weight kg/mtr	Application	End Pull Resistance kg	Price \$ per m
	ID	OD								
A820HW100	102	126	300	20	1200	500	6.2	Suction/Delivery	5000	376.49
A820HW125	127	153	300	20	1200	625	8.5	Suction/Delivery	5000	473.26

Price Group: HR  
DB46

## RigBoss™ Series - Dry Cement - Barite (A820S)




Application:	Rugged but flexible soft wall hose featuring high abrasive resistant tube designed for transfer of dry cement and barytes. Hose features 5,000kg end pull resistance.
Tube:	Black SBR/NR blend, abrasion, ozone resistant, static conductive
Reinforcement	High tensile textile cords
Cover:	Black CR; abrasion, ozone resistant, static conductive
Temperature:	-20°C to 80°C
Lengths:	20 mtr, 40 mtr and 61 mtr

### Soft Wall

Part No.	Dimensions (mm)		Working Pressure PSI	Bar	BP PSI	Bend Radius (mm)	Weight kg/mtr	Application	End Pull Resistance kg	Price \$ per m
	ID	OD								
A820SW100	102	126	300	20	1200	800	4.8	Delivery	5000	318.00
A820SW125	127	153	300	20	1200	1000	3.5	Delivery	5000	424.35

Price Group: HR  
DB46

## RigBoss™ Series - Potable Water (A620H)




Application:	Rugged but flexible hard wall hose designed for transfer of potable water. Hose features 5,000kg end pull resistance.
Tube:	White NR
Reinforcement	High tensile textile cords with embedded steel wire and helix wire
Cover:	Orange CR - abrasion and ozone
Temperature:	-40°C to 80°C
Lengths:	20 mtr, 40 mtr and 61 mtr

### Hard Wall

Part No.	Dimensions (mm)		Working Pressure PSI	Bar	BP PSI	Bend Radius (mm)	Weight kg/mtr	Application	End Pull Resistance kg	Price \$ per m
	ID	OD								
A620HW050	50	70	300	20	1200	250	3.2	Suction/Delivery	5000	219.08
A620HW080	76	97	300	20	1200	350	4.0	Suction/Delivery	5000	288.22
A620HW100	102	125	300	20	1200	500	5.8	Suction/Delivery	5000	500.92
A620HW125	127	152	300	20	1200	1200	8.4	Suction/Delivery	5000	706.18

Price Group: HR  
DB46

## RigBoss™ Series - Potable Water (A620S)



Application:	Rugged but flexible hard wall hose designed for transfer of potable water. Hose features 5,000kg end pull resistance.
Tube:	White NR
Reinforcement	High tensile textile cords
Cover:	Orange CR - abrasion and ozone
Temperature:	-40°C to 80°C
Lengths:	20 mtr, 40 mtr and 61 mtr

### Soft Wall

Part No.	Dimensions (mm)		Working Pressure PSI	Bar	BP PSI	Bend Radius (mm)	Weight kg/mtr	Application	End Pull Resistance kg	Price \$ per m
	ID	OD								
A620SW100	50	68	300	20	1200	400	3.0	Delivery	5000	407.33
A620SW125	76	97	300	20	1200	560	3.7	Delivery	5000	632.80
A620SW125	102	125	300	20	1200	800	5.2	Delivery	5000	632.80
A620SW125	127	152	300	20	1200	1000	7.7	Delivery	5000	632.80

Price Group: HR  
DB46

Complete hose data specification sheets are available upon request.