

King Crimp™ EZ Boss-Lock™ Domestic Cam & Groove Type C

Features: Couplers are supplied standard with a Buna-N gasket. Other gasket types are available, refer to pages 106-107.

Female Coupler x Hose Shank

Hose ID (inch)	316 Stainless Steel Part No.	Price \$
1	RC100EZCR	158.16
1½	RC150EZCR	205.25
2	RC200EZCR	312.39
3	RC300EZCR	304.02
4	RC400EZCR	583.31
6	RC600EZCR	949.50

Price Group: SD
AL03



B



Under no circumstances should the EZ Boss-Lock™ cam arms be used on any fittings not specifically designed for their use. Refer to pages 107 & 118 for further specifications.

Cam & Groove Type C

Features:

- All couplers are supplied with safety clips.
- Couplers are supplied standard with a Buna-N gasket. Other gasket types are available, refer to pages 106-107.

Female Coupler x Hose Shank

Hose ID (inch)	A380 Permanent Mould Aluminium		ASTMC 3800 Forged Brass		316 Investment Cast Stainless Steel	
	Part No.	Price \$	Part No.	Price \$	Part No.	Price \$
1	G100-C-ALCR	21.16	G100-C-BRCR	52.47	G100-C-SSCR	53.65
1½	G150-C-ALCR	36.42	G150-C-BRCR	79.43	G150-C-SSCR	94.65
2	G200-C-ALCR	31.93	G200-C-BRCR	86.94	G200-C-SSCR	138.10
3	G300-C-ALCR	57.33	G300-C-BRCR	115.41	G300-C-SSCR	189.95
4	G400-C-ALCR	74.00	G400-C-BRCR	227.05	G400-C-SSCR	326.08
6	G600-C-ALCR	266.13	-	-	G600-C-SSCR	836.17

Price Group: SD
AL15



Cam & Groove Type E

Male Adaptor x Hose Shank

Hose ID (inch)	A380 Permanent Mould Aluminium		ASTMC 3800 Forged Brass		316 Investment Cast Stainless Steel	
	Part No.	Price \$	Part No.	Price \$	Part No.	Price \$
1	G100-E-ALCR	12.56	G100-E-BRCR	38.60	G100-E-SSCR	54.84
1½	G150-E-ALCR	21.42	G150-E-BRCR	77.89	G150-E-SSCR	100.98
2	G200-E-ALCR	20.41	G200-E-BRCR	74.13	G200-E-SSCR	124.70
3	G300-E-ALCR	28.63	G300-E-BRCR	96.71	G300-E-SSCR	186.57
4	G400-E-ALCR	58.84	G400-E-BRCR	288.87	G400-E-SSCR	232.43
6	G600-E-ALCR	218.84	G600-E-BRCR	340.83	G600-E-SSCR	835.85

Price Group: SD
AL15



• Refer to crimp sleeves and ferrules on pages 190-193.



Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, DO NOT interchange other manufacturer's products with Dixon™ products.