

'A' Type - Bellow Seal 1000 PSI - SG Iron

minsup

1000
PSI

C

Feature:	Standard coupling heads ensure the interchangeability of all sizes, regardless of whether the mating coupling is male, female or hose tail.
Options:	Other seal materials available on request NPT threads available for Male and Female threaded couplings

Size (inch)	Pkg Qty	Male BSP	
		Part No.	Price \$ (ea)
3/8	50	ABS10M	17.31
1/2	50	ABS15M	14.47
3/4	50	ABS20M	14.47
1	50	ABS25M	14.47
1 1/4	40	ABS32M	19.95

Price Group: MS
AA01



Size (inch)	Pkg Qty	Female BSP	
		Part No.	Price \$ (ea)
3/8	50	ABS10F	17.31
1/2	50	ABS15F	14.47
3/4	50	ABS20F	14.47
1	50	ABS25F	14.47

Price Group: MS
AA01



Size (inch)	Pkg Qty	Hose End	
		Part No.	Price \$ (ea)
3/8	50	ABS10H	17.31
1/2	50	ABS15H	14.47
3/4	50	ABS20H	14.47
1	50	ABS25H	14.47
1 1/4	40	ABS32H	19.95

Price Group: MS
AA01



For Minsup Safety Claw Clamps, refer to page 216.

For ring crimp ferrules, refer to page 125.



- 'A' type bellow seal couplings are not recommended for use with Minsup™ standard seal couplings.
- **WARNING:** Never use 'A' Type Couplings for steam service! None of Dixon™'s catalogue information is to be interpreted to mean that this type of coupling is suitable for use on steam hose.

FOR SPECIFICATIONS, APPLICATION AND MATERIAL GUIDELINES PLEASE REFER TO PAGE 114



1300 134 651
dixonvalve.com.au

All prices exclude GST.
ADPL718