

Holedall Uni-Range External Couplings



Designed for smaller hose systems, these couplings may be used for hose I.D.'s of 6mm - 25mm and come complete with factory assembled stem and ferrule combination. Can be used with Swage or Crimp equipment.

Plated Carbon Steel Stem, Ferrule					
ID & NPTF Size (mm)	Hose OD (mm)		Part No.		Price \$
	From:	To:			
6	13	15	4P1	i	16.61
6	15	17	4P2	i	16.61
6	17	18	4P3	i	16.61
10	18	20	6P1	i	21.94
10	20	21	6P2	i	21.94
10	21	23	6P3	i	21.94
15	21	23	8P1		31.62
15	23	25	8P2		29.76
15	25	30	8P3		30.58
20	29	31	12P1	i	34.05
20	31	32	12P2	i	38.66
20	32	37	12P3	i	39.54
25	37	39	16P1	i	68.15
25	39	40	16P2	i	54.23
25	40	42	16P3	i	43.63
25	42	44	16P4	i	43.63


Other sizes available on special order.

Price Group: PC

Holedall High Pressure Couplings



The LM tubular stem with NPT end and ferrule



Use these couplings for services requiring a fitting which will withstand extremely high pressures (up to 3,000 PSI) and severe operating conditions, such as on small and medium size drilling rigs, used for Slim Hole, Core Drill, Workover, Seismograph, Water Well, Blast or Shot Holes, etc. These extra long, rugged fittings are machined from seamless pipe and tubing with specially designed serrations. The mating ferrules are machined from heavy wall material incorporating matching serrations and rows of set screws for better coupling retention. These couplings are shipped with matching ferrules. Please provide hose O.D. when ordering for properly sized ferrule. Make sure both ends of the hose are measured for O.D. Must be swaged with 50 Ton or 100 Ton Ram.

N
305 - 322

Stem / Ferrule Assemblies			
ID & NPT Size (mm)	Part No.		Price \$
50	LM32	i	POR
65	LM40	i	POR
75	LM48	i	POR
ID & API Size (mm)	Part No.		Price \$
50 x 65	LM3240	i	POR
65 x 75	LM4048	i	POR
75 x 100	LM4864	i	POR

*The LM fitting is sold as a complete coupling including stem and ferrule. Accurate hose O.D. must be provided to complete the part # and to insure proper retention.

Price Group: SD

AU03