

## Crimp Style Heavy Duty Ferrules



NEW!

### Features:

400psi working pressure with a minimum 4:1 safety factor (hose burst:hose working pressure) is only achieved with Dixon carbon steel ferrule part numbers CF400-6CSHD through CF400-16CSHD.

C

81 - 89

Hose ID (inch)	Hose OD (mm)		Carbon Steel - Heavy Duty (HD)		Ferrule ID (mm)	Ferrule Wall Thickness (mm)	Ferrule Overall Length (mm)	
	From	To	Part No.	Price \$				
4	114.70	115.90	CF400-6CSHD	i	25.28	117.48	3.05	101.60
4	116.30	117.50	CF400-7CSHD	i	29.80	117.48	3.05	101.60
4	117.90	119.10	CF400-8CSHD	i	29.80	117.48	3.05	101.60
4	119.50	121.70	CF400-9CSHD	i	29.80	117.48	3.05	101.60
4	121.00	122.25	CF400-10CSHD	i	29.80	117.48	3.05	101.60
4	122.60	123.85	CF400-11CSHD	i	30.80	117.48	3.05	101.60
4	124.20	125.40	CF400-12CSHD	i	30.80	117.48	3.05	101.60
4	125.80	127.00	CF400-13CSHD	i	30.80	117.48	3.05	101.60
4	124.40	128.60	CF400-14CSHD	i	30.80	117.48	3.05	101.60
4	129.00	130.20	CF400-15CSHD	i	31.30	117.48	3.05	101.60
4	130.60	131.80	CF400-16CSHD	i	31.30	117.48	3.05	101.60

Price Group: SD

AU06

## Crimp Style King Combination Nipples



NEW!

### Features:

There are two grooves on the crimp style King Combination nipples. The second groove is the roll stamp groove which has the part number and "call Dixon" stamped on it. This groove is a smooth concentric groove so that the stamp can be legible.

Threaded End						
Hose ID (inch)	Schedule 80 Plated Carbon Steel			316 Stainless Steel		
	Part No.	Price \$		Part No.	Price \$	
NPT						
1	STC10CS	i	36.43	RST10CS	47.61	
1¼	STC15CS	i	26.50	RST15CS	i	39.70
1½	STC20CS		18.42	RST20CS	56.51	
2	STC25CS		21.53	RST25CS	i	65.41
3	STC35CS		54.65	RST35CS	214.25	
4	STC40CS		72.45	RST40CS	328.20	
6	STC60CS		139.31	RST60CS	791.36	
BSP						
1	STC10CSA		32.81	RSTC10CSA	82.28	
1¼	STC15CSA	i	26.50	RSTC15CSA	i	51.60
1½	STC20CSA		34.88	RSTC20CSA	100.08	
2	STC25CSA		36.33	RSTC25CSA	133.52	
3	STC35CSA		76.80	RSTC35CSA	366.91	
4	STC40CSA		90.67	RSTC40CSA	550.41	
6	STC60CSA		153.28	RSTC60CSA	836.80	

Price Group: SD

AM10



SAFETY ALERT

Only use the crimp style shanks with the crimp style sleeves and ferrules.

Due to differences in dimensions and tolerances for safety reasons, DO NOT interchange other manufacturer's products with Dixon products.