

Surelock - Stainless Steel minsup

Application: The Minsup surelock stainless steel couplings are high quality precision cast fittings suitable for corrosive environments.

Surelock Working Pressure Rates

Size (inch)	Working Pressure		Burst Pressure	
	psi	MPa	psi	MPa
3/8 - 1/4	1000	6.9	4000	27.58
1 1/2 - 2	1000	6.9	4000	27.58



Male BSP

Size (inch)	Pkg Qty	Part No.	Price \$ (ea)
Small Head			
1/2	50	SM13BSPSTS	98.33
3/4	50	SM20BSPSTS	98.33
1	50	SM25BSPSTS	98.33
Medium Head			
1 1/2	15	SM38BSPSTS	i POR
2	15	SM50BSPSTS	174.19

Price Group: SD
AA03
AA04

Female BSP

Size (inch)	Pkg Qty	Part No.	Price \$ (ea)
Small Head			
1/2	50	SF13BSPSTS	98.33
3/4	50	SF20BSPSTS	98.33
1	50	SF25BSPSTS	98.33
Medium Head			
1 1/2	15	SF38BSPSTS	i POR
2	15	SF50BSPSTS	181.69

Price Group: SD
AA03
AA04

Hose End

Size (inch)	Pkg Qty	Part No.	Price \$ (ea)
Small Head			
1/2	50	SH13STS	98.33
3/4	50	SH20STS	98.33
1	50	SH25STS	98.33
Medium Head			
1 1/2	15	SH38STS	i POR
2	15	SH50STS	169.95

• NPT Male and Female available on request
• 1 1/2 BSP available while stocks last
Price Group: SD
AA03
AA04



WARNING: Never use Couplings for steam service! None of Dixon's catalogue information is to be interpreted to mean that this type of coupling is suitable for use on steam hose.

FOR SPECIFICATIONS, APPLICATION AND MATERIAL GUIDELINES PLEASE REFER TO PAGE 150



Phone: 1300 134 651
www.dixonvalve.com

ADPL2013-14

Part numbers marked "i" are non stock.
Enquire for availability.
All prices exclude GST.

G
149 - 196