


Mini Ball Valves



art.125



art.126

Design:	Blow-out proof stem with chrome ball
End Connection:	Screwed Female & Male/ Female BSP ISO228 (equivalent to DIN259 and BS2779)
Body Materials:	Nickel-plated brass
Seat & Trim:	PTFE Seats
Temperature:	-0°C - 90°C. Rated to 220PSI
Application:	Domestic water services, heating and air-conditioning plants, compressed air systems

Female BSP x Female BSP						
Size		Part No.		Working Pressure		Price \$
inch	mm			PSI	MPa	
1/8	3	MBF003	i	220	1.5	14.87
1/4	6	MBVFF006		220	1.5	11.96
3/8	10	MBVFF010		220	1.5	11.48
1/2	15	MBVFF012		220	1.5	14.47
3/4	20	MBVFF020		220	1.5	22.76

Price Group: SD

Female BSP x Male BSP						
Size		Part No.		Working Pressure		Price \$
inch	mm			PSI	MPa	
1/8	3	MBM003	i	220	1.5	16.15
1/4	6	MBVMF006		220	1.5	11.96
3/8	10	MBVMF010		220	1.5	11.48
1/2	15	MBVMF012		220	1.5	14.47
3/4	20	MBVMF020		220	1.5	22.76

Price Group: SD

AR01

Lockable Ball Valve



Design:	Lever operated, C/W Locking device, for lock open or lock closed.
End Connection:	Screwed Female BSP
Body Materials:	Brass, Nickel Plated
Seat & Trim:	PTFE seats
Temperature:	-10 to 110°C
Application:	For Industrial Pneumatic and Hydraulic applications. Water, oil & gas
Approvals:	AGA and Watermark

Size		Part No.	Price \$
inch	mm		
1/2	15	V15LO	19.19
3/4	20	V20LO	24.72
1	25	V25LO	43.26
1 1/4	32	V32LO	70.62
1 1/2	40	V40LO	106.69
2	50	V50LO	167.84

Price Group: FE

VB06

S
453 - 499