# DATA SHEET

# A102 Rubber Contractors Air Delivery Hose



The Hight Connection

Crafted with a smooth yellow non-marking cover to enhance visibility, this cost-effective pneumatic air and water hose is tailored for diverse applications in construction, industrial, and agricultural fields. It's particularly well-suited for heavy-duty air compressor usage, seamlessly supporting a wide range of pneumatic equipment such as portable compressors, jackhammers, breakers, and stampers.



## **Hose Construction**

**Tube:** SBR blend - black

**Cover:** SBR blend, smooth - yellow

Reinforcing: Polyester yarn

### **Features**

- · Oil mist resistant
- Ozone resistant
- · Weather resistant
- · Abrasion resistant
- Extruded

# **Temperature**

• -25°C to 75°C

### **Standards**

Nil

### **Part Number**

• To view available part number options please click here

Dimensions (mm)		Pressures					Bend		
		Working		Burst		Vacuum (bar)	Radius	Weight (kg/mtr)	Coil
ID	OD	PSI	Bar	PSI	Bar		(mm)	(9,)	Lengths
IO						)(		<b>€</b>	(mtr)
6.4	13.0	200	14	696	48	n/a	50	0.18	20, 100
9.5	17.0	200	14	696	48	n/a	75	0.26	20, 100
12.7	21.0	200	14	696	48	n/a	100	0.39	20, 100
15.9	26.0	200	14	696	48	n/a	125	0.56	20, 100
19.1	31.0	200	14	696	48	n/a	155	0.83	20, 100
25.4	37.0	200	14	696	48	n/a	205	0.92	20, 100

Product Group: DB43