DATA SHEET

A115 Fuel Line Delivery Hose



A high quality reinforced rubber hose designed to meet the requirements of SAE 30R7, suitable for a range of applications such as flexible fuel lines, PCV connections, emission control lines, or fuel return lines. Compatible with fuels containing a maximum of 50% aromatic content including leaded and unleaded gasoline, diesel fuel, and gasoline blends of ethanol (E-10).



Hose Construction

Tube:NBR blend - blackCover:NBR blend, smooth - blackReinforcing:Polyester yarn

Features

- Ozone resistant
- Weather resistant
- · Oil resistant
- Extruded

Temperature

• -20°C to 70°C

Standards

• SAE 30R7

Part Number

• To view available part number options please click here

Dimensions (mm)		Pressures					Bend		
		Working		Burst		Vacuum (bar)	Radius	Weight (kg/mtr)	Coil
ID	OD	PSI	Bar	PSI	Bar	(Dai)	(mm)	(Ng/IIII)	Lengths
IO)(₩	(mtr)
4.8	11.0	100	7	400	28	n/a	40	0.12	30
6.4	13.0	100	7	400	28	n/a	50	0.15	30
7.9	15.0	100	7	400	28	n/a	65	0.19	30
9.5	17.0	100	7	400	28	n/a	75	0.23	30
12.7	20.0	100	7	400	28	n/a	100	0.28	30

Product Code: DB13