DATA SHEET A214 Contractors Water Suction & Delivery Hose

The Right Connection®

AQUABOSS

Water suction and delivery hose used for water, sewage and slurry discharge applications. Short-length hoses are produced with cuffed ends for easier coupling assembly.



Hose Construction

Tube: SBR - black Cover: SBR/EPDM blend - black **Reinforcing:** High tensile synthetic textile cords, single wire helix

Features

- Corrugated cover
- Ozone resistant
- Weather resistant
- Abrasion resistant
- Oil mist resistant
- Mylar layline & embossed tape line
- Mandrel built

Temperature

• -30°C to +80°C

Standards

• Nil

Part Number

• To view available part number options please click here

| Dimensions (mm) | | Positive Working Pressure PSI / Bar | | | | | | Bend | |
|--------------------|------------|-------------------------------------|-----|-------|-----|-----------------|--------------------|--------|----------------|
| | | Working | | Burst | | Vacuum (bar) | Weight (kg/mtr) | Radius | Coil |
| ID | OD | psi | bar | psi | bar | (Bul) | (| (mm) | Length |
| IO | \bigcirc | \bigcirc | | ×. | |)(| M | | (mtr) |
| 76.2 | 87 | 75 | 5 | 225 | 15 | 0.8 | 2.68 | 305 | 6, 20 |
| 101.6 | 115 | 75 | 5 | 225 | 15 | 0.8 | 3.59 | 500 | 6, 20 |
| 127.0 | 142 | 75 | 5 | 225 | 15 | 0.8 | 5.61 | 750 | 20 |
| 152.4 | 168 | 75 | 5 | 225 | 15 | 0.8 | 7.04 | 960 | 3, 20 |
| 203.2 | 225 | 75 | 5 | 225 | 15 | 0.8 | 9.24 | 1200 | 3, 20 |
| | | | | | | | | Produ | ict Code: DB17 |

Product Code: DB17