DATA SHEET

A450 Petrol & Oil Delivery Hose



Specially designed for the transfer of petroleum/oil products with a maximum of 50% aromatic content. Typically used on tank trucks and in general industrial applications. Suitable for use in some reeling applications.



Hose Construction

Tube: NBR - black

Cover: SBR/EPDM smooth blend - black Reinforcing: High tensile synthetic textile cords with

anti-static copper wires

Features

- Ozone resistant
- Weather resistant
- Abrasion resistant
- Oil resistant
- Mylar layline & embossed tape line
- · Mandrel built

Temperature

• -35°C to 80°C

Standards

Nil

Part Number

• To view available part number options please click here

Dimensions (mm)		Pressures						Bend	
		Working		Burst		Vacuum (bar)	Weight (kg/mtr)	Radius	Coil
ID	OD	PSI	Bar	PSI	Bar	(Dai)	(Rg/IIII)	(mm)	Lengths
IO)(₩		(mtr)
19.1	30	150	10	450	30	n/a	0.62	240	20
25.4	37	150	10	450	30	n/a	0.82	300	20, 60
31.8	44	150	10	450	30	n/a	1.05	385	20, 60
38.1	51	150	10	450	30	n/a	1.29	455	20, 60
50.8	64	150	10	450	30	n/a	1.64	610	20
63.5	75	150	10	450	30	n/a	1.76	760	20
76.2	90	150	10	450	30	n/a	2.47	910	20

Product Code: DB13