DATA SHEET A710 FRAS Air & Water Suction & Delivery Hose

The Right Connection®

113

MINEBOSS

Designed to meet the fire-resistant and anti-static (FRAS) requirements of AS2660 for air and water suction and discharge in underground coal mines. Also suitable for use as a water and light slurry suction and delivery hose in construction, mining, dewatering, irrigation, and municipal applications.



Hose Construction

Tube: Cover: Reinforcing: NBR blend - black Chloroprene blend smooth - black High tensile synthetic textile cords & steel wire helix

Features

- Weather resistant
- Ozone resistant
- Abrasion resistant
- Oil mist resistant
- Mylar layline & embossed tape line
- Fire resistant
- Anti-static as per AS2660 Class C
- Electrically conductive resistance <1 M Ω /m

Temperature

-30°C to 70°C

Standards

• AS 2660 Class C

Part Number

• To view available part number options please <u>click here</u>

Coil Lengths (mtr)	Bend Radius (mm)	Weight (kg/mtr)	Vacuum (bar)	Pressures				Dimensions	
				Burst		Working		(mm)	
				Bar	PSI	Bar	PSI	OD	ID
				×.		\bigcirc			
20	150	1.22	0.9	30	450	10	150	48.0	38.1
20	215	1.95	0.9	30	450	10	150	63.0	50.8
20	280	2.31	0.9	30	450	10	150	75.0	63.5
20	350	2.99	0.9	30	450	10	150	89.0	76.2
20	490	4.15	0.9	30	450	10	150	116.0	101.6
20	760	8.53	0.9	30	450	10	150	168.0	152.4

Product Code: DB41