



The Right Connection®

# API Drop Adapters

## Application

- For offloading petroleum cargo tanks through the API adapter to 3" or 4" drop hoses


## Feature

- Compatible with most API adapters

## Specification

- Maximum operating pressure: 75psi


Description	Fuel Compatibility	Part #
API to 3" drop adapter, Baylast™ O-ring seal	Gasoline and diesel, up to E100 and B100 biofuels	4530
API to 3" drop adapter, no sight glass, Buna-N flat gasket		4530G
API to 3" drop adapter, Buna-N flat gasket, with inline sight glass		4530SG
API to 4" drop adapter, Baylast™ O-ring seal		4540
API to 4" drop adapter, FKM O-ring seal	Gasoline and diesel, up to B100 biodiesel	4540V
API to 4" drop adapter, no sight glass, Buna-N flat gasket	Gasoline and diesel, up to E100 and B100 biofuels	4540G
API to 4" drop adapter, Buna-N flat gasket, one piece, with inline sight glass		4540SG
API to 4" drop adapter, FKM flat gasket, inline sight glass	Gasoline and diesel, up to B100 biodiesel	4540SGV
API to 4" drop coupler, Buna-N gasket		4540F
TTMA to 4" drop adapter, Baylast™ seals, with sight glass	Gasoline and diesel, up to E100 and B100 biofuels	4502
API to 4" drop adapter, Baylast™ O-ring with sight glass, two-piece design		4502ASSM
API to 4" drop coupler, Baylast™ gasket with sight glass, two-piece design		4504ASSM



4540




4540G



4540SG



4540F



4502ASSM



4502

**Dixon**

1300 134 651

Customerservice@dixonvalve.com.au

[dixonvalve.com.au](http://dixonvalve.com.au)

NOTE: Dixon offers both O-ring and flat gasket styles.

