Data Sheet DOT Air Brake Fittings for Rubber Air Hose





DOT Air Brake Fittings - Rubber Air Hose

56RBSG-06 56RBSG-08	3/8" hose spring 1/2" hose spring
60RB-06 60RB-08	3/8" sleeve 1/2" sleeve
61RB-06 61RB-08 61RBSG-06 61RBSG-08	3/8" nut 1/2" nut 3/8" spring guard nut 1/2" spring guard nut
67RBSG-06 67RBSG-08	3/8" nut with attached spring 1/2" nut with attached spring
68RB-0604B 68RB-0606B 68RB-0608B 68RB-0806B 68RB-0808B	3/8" male connector* 3/8" male connector* 3/8" male connector* 1/2" male connector* 1/2" male connector*
68RBSG-0604 68RBSG-0606 68RBSG-0608 68RBSG-0806 68RBSG-0808	3/8" male connector with spring guard* 3/8" male connector with spring guard* 3/8" male connector with spring guard* 1/2" male connector with spring guard* 1/2" male connector with spring guard*

^{*} Contact Dixon at dixonvalve.com for different thread sizes

Compliances:

 Will meet DOT FMVSS 571-106 standards when used with SAE J1402 air brake hose

Material

· Brass: Alloy 360

Performance

- Working pressure: up to 225 PSI
- · Operating temperature range: -50°F to 212°F

Application / Market

For use with SAEJ1402 air brake hose in making hose assemblies

Assembly Guide

- · Slide nut onto hose
- Slide sleeve onto hose with tapered edge toward fitting body
- Firmly bottom the hose into fittings
- Screw nut onto body until it contacts the fitting body's hex

Dixon Brass

40 Chestnut Ave, Westmont, IL, 60559 ph: 800.323.4440 fx: 800.628.7259 dixonvalve.com