DATA SHEET

# A104 Rubber Multi-Purpose Delivery Hose

The Right Connection®

Designed with economy in mind, this high quality non-conductive, multi-purpose, extruded rubber hose is the perfect choice for conveying air, oil, water, kerosene, some chemicals and many other applications where the need for oil resistance is high. The versatility of this hose makes it an excellent choice in a range of applications and industries.

**Hose Construction**

**Tube:** NBR blend - black
**Cover:** NBR blend - red, blue or yellow
**Reinforcing:** Polyester yarn

**Features**

- UV stabilised
- Oil resistant
- Non-conductive
- Extruded

**Temperature**

- -20°C to 100°C

**Standards**

- Nil

**Part Number**

- To view available part number options please click here

| Dimensions (mm) | | Pressures | | | | Vacuum (bar) | Bend Radius (mm) | Weight (kg/mtr) | Coil Lengths (mtr) |
|---|---|---|---|---|---|---|---|---|---|
| | | Working | | Burst | | | | | |
| ID | OD | PSI | Bar | PSI | Bar | | | | |
| 6.4 | 15.9 | 300 | 20 | 1200 | 80 | n/a | 50 | 0.29 | 20, 100 |
| 7.9 | 17.0 | 300 | 20 | 1200 | 80 | n/a | 65 | 0.28 | 20, 100 |
| 9.5 | 18.2 | 300 | 20 | 1200 | 80 | n/a | 75 | 0.30 | 20, 100 |
| 12.7 | 22.0 | 300 | 20 | 1200 | 80 | n/a | 100 | 0.40 | 20, 100 |
| 15.9 | 26.0 | 300 | 20 | 1200 | 80 | n/a | 125 | 0.52 | 20, 100 |
| 19.1 | 30.2 | 300 | 20 | 1200 | 80 | n/a | 155 | 0.67 | 20, 100 |
| 25.4 | 38.0 | 300 | 20 | 1200 | 80 | n/a | 205 | 1.00 | 20, 100 |
| 31.8 | 45.0 | 250 | 17 | 1000 | 68 | n/a | 255 | 1.25 | 30 |
| 38.1 | 53.0 | 250 | 17 | 1000 | 68 | n/a | 305 | 1.68 | 30 |
| 50.8 | 67.0 | 200 | 14 | 800 | 56 | n/a | 405 | 2.36 | 30 |

Product Code: DB18

customerservice@dixonvalve.com.au . 1300 134 651