DATA SHEET

# H080 PVC Fire Reel Delivery Hose

The Right Connection®

Designed with excellent flexibility, UV resistance, and self-extinguishing capabilities, this product is manufactured in accordance with AS/NZS 1221:1997 standards, specifically tailored for utilisation on fire reels.

**Hose Construction**

| | |
|---|---|
| **Tube:** | PVC - black |
| **Cover:** | PVC, ribbed - black |
| **Reinforcing:** | Polyester yarn |

**Features**
- UV stabilised
- Abrasion resistant
- Self extinguishing

**Temperature**
- -5°C to 60°C

**Standards**
- AS/NZS 1221:1997

**Part Number**
- To view available part number options please click here

| Dimensions (mm) | | Pressures | | | | Vacuum (bar) | Bend Radius (mm) | Weight (kg/mtr) | Coil Lengths (mtr) |
|---|---|---|---|---|---|---|---|---|---|
| | | Working | | Burst | | | | | |
| ID | OD | PSI | Bar | PSI | Bar | | | | |
| 19.1 | 26.0 | 145 | 10 | 580 | 40 | n/a | 228 | 0.37 | 20, 36, 100 |
| 25.4 | 33.0 | 145 | 10 | 580 | 40 | n/a | 300 | 0.55 | 20, 36, 100 |

Product Code: DA06