DATA SHEET

MAR PVC Water Suction & Delivery Hose

The Right Connection*

Designed with a smooth bore to reduce friction loss and build-up of residue, this lightweight suction and discharge hose is well suited for use with bilge pumps and pond pumps. Its versatility sees it commonly used as a waste water hose for caravans and RV's, a lightweight air seeder hose, ducting for dust extraction and a low voltage cable conduit.



Hose Construction

 Tube:
 PV

 Cover:
 PV

 Reinforcing:
 PV

PVC - black PVC corrugated - black g: PVC embedded rigid helix - black

Features

- UV stabilised
- Abrasion resistant
- Non-toxic
- Food grade FDA approved
- Extruded

Temperature

-5°C to 60°C

Standards

• Nil

Part Number

• To view available part number options please click here

Coil Lengths	Bend Radius (mm)	Weight (kg/mtr)	Vacuum (bar)	Pressures				Dimensions	
				Burst		Working		(mm)	
				Bar	PSI	Bar	PSI	OD	ID
				×		\bigcirc			
20	90	0.16	0.4	6	90	2	30	24.5	19.1
20	95	0.22	0.4	6	90	2	30	31.0	25.4
20	105	0.25	0.4	6	90	2	30	34.0	28.0
20	115	0.28	0.4	6	90	2	30	37.0	31.8
20	140	0.34	0.4	6	90	2	30	45.0	38.1
20	180	0.55	0.4	6	90	2	30	59.0	50.8
20	220	0.78	0.4	6	90	2	30	86.0	76.2

Product Code: DA17