

King Cable™

D

Application:	These strong steel cables prevent hose whip in case of accidental separation of coupling or clamp device. King Cable™ reaches across the hose fittings to provide stand by safety for hose. Spring-loaded loops in the cable ends open easily to pass over the couplings for a firm grip on the hose. Thoroughly tested with years of service. King Cable™ should be installed in the extended position (no slack).
Features	<ul style="list-style-type: none"> • Must be installed in the extended position (no slack). • Cable reaches across hose fittings to provide standby safety for hose. • Spring-loaded loops open easily to pass over the couplings for a firm grip on the hose. • No tools needed - easy to install and remove. • Cables shipped with safety restraint labels attached. • Highly resistant to rust and corrosion. • Hose-to-hose or hose-to-rigid outlet. • Maximum operating pressure: 200 PSI. • Minimizes damage to equipment and injuries to operators in the event hose, couplings or clamps fail, or there is an accidental separation of the assembly.
Materials:	galvanized steel wire rope, aluminium ferrules, galvanized carbon steel springs

Hose End



Tool End

Style WSR for Hose to Tool Service

Cable (mm)	Hose ID (mm)	Length (mm)	Steel		316 Stainless Steel	
			Part No.	Price \$ (ea)	Part No.	Price \$ (ea)
3	13 - 32	515	WSR1	16.39	WSR1SS	39.28
5	13 - 50	712	WSR3	67.17	---	---
6	38 - 75	956	WSR2	32.51	WSR2SS	111.32
10	100	1118	WSR4	93.53	---	---

Price Group: SD
AD03

Hose End



Hose End

Style WSR for Hose to Hose Service

Cable (mm)	Hose ID (mm)	Length (mm)	Steel		316 Stainless Steel	
			Part No.	Price \$ (ea)	Part No.	Price \$ (ea)
3	13 - 32	515	WB1	17.46	WB1SS	36.10
5	13 - 50	712	WB3	24.46	---	---
6	38 - 75	956	WA2	41.58	WA2SS	101.10
10	100	1118	WA4	61.79	---	---

Price Group: SD
AD03



- Use King Cable™ to help prevent accidents or injuries resulting from hose or coupling failure.
- A positive Safeguard For Air Hose Connections - Helps You Meet Today's Safety Standards



WSR1E

Other King Cable™ Options

Cable (mm)	Part No.	Description	Materials	Price \$ (ea)
3	WSR1E	WSR1 with stainless steel safety marine eye used to connect safety cable to a bolt on tool.	galvanized carbon steel wire rope, aluminum ferrules, galvanized carbon steel springs	107.00

Price Group: SD
AD03