Dixon[™] Frac Fittings

Application:	Used in the fast paced transfer of water and sand slurry to a hydraulic fracturing site.
Features:	 One-piece design eliminates leak path experienced with two-piece threaded systems. Interchangeable with current fittings; phase them into your current operation. Long lasting and dependable hammer nut is forged to ASTM 105N standards. Machined malleable iron stems to ASTM A47 standard. Durable and safe with reliable hose retention when crimped as specified. 400 PSI working pressure at 21°C 400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with Dixon™ carbon steel ferrule part numbers CF400-6CSHD through CF400-16CSHD, refer to page 151. When assembling hose with abrasion covers, such as UHMW polyethylene, you will need to use Dixon™'s heavy duty (HD) carbon steel ferrule part numbers CF400-6CSHD through CF400-16CSHD, refer to page 151.
Material:	All stems are zinc plated

Figure 206

Description

socket weld x suction male hammer union

socket weld x suction female hammer union

split nut, suction and discharge, black

(includes O-ring, no nut)

Part No.

HUSM500SW-1

HUSF500SW

HUS500RN

Suction Service Fittings





HUSF500SW

Dixon™ Figure 206 O-rings

Size (inch)

5

Figure

50

50

N/A



Figure 206									
Size (inch)	Description	Part No.	Price \$	Material					
2	Figure 206 O-ring	O288BU	10.00						
3	Figure 206 O-ring	O238BU	12.70						
4	Figure 206 O-ring	O347BU	15.22	Buna-N					
4	Figure 206 Cap O-ring	O429BU	11.40						
6	Figure 206 O-ring	O440BU	12.60						
8	Figure 206 O-ring	O447BU	10.94						

Price Group: SD AN08

Price \$

305.45

391.80

200.54 Price Group: SD

AN08

King Crimp[™] Style Short Frac Ferrules

Carbon Steel										
Hose ID	Hose OD		Ferrule Wall	Ferrule ID	Ferrule Over-	Part No.	Price \$			
	From	То	Thickness	renule ID	all Length	Fart NO.	Flice ø			
	8-29/64"	8-36/64"	.120"	8.625"	4.25"	CFS800-1CS	156.16			
	8-37/64"	8-44/64"	.120"	8.750"	4.25"	CFS800-2CS	156.16			
8"	8-45/64"	8-52/64"	.120"	8.875"	4.25"	CFS800-3CS	156.16			
	8-53/64"	8-60/64"	.120"	9.000"	4.25"	CFS800-4CS	156.16			
0	8-61/64"	9-4/64"	.120"	9.125"	4.25"	CFS800-5CS	156.16			
	9-5/64"	9-12/64"	.120"	9.250"	4.25"	CFS800-6CS	156.16			
	9-13/64"	9-20/64"	.120"	9.375"	4.25"	CFS800-7CS	156.16			
	9-21/64"	9-28/64"	.120"	9.500"	4.25"	CFS800-8CS	156.16			

Price Group: SD

AN06

