¹⁸⁴ Industrial Hose Fittings

Ground Joint Accessories Boss™ Adaptors



Boss™ Male NPT Adaptor							
Size (inch)	Size (mm)	Part No.	Price \$				
3/4	20	GMAS6	166.07				
1	25	GMAS11	165.81				
11/2	40	GMAS21	234.19				
2	50	GMAS26 ¹	225.13				
¹ GMAS26 takes a sp	Price Group: SD						

AD01

Boss™ Female NPT Adaptor						
Size (inch)	Part No.	Price \$				
3/4	GFAS6	156.39				
1	GFAS11	125.00				
Wing nut is permanently attache	ed on the 1" size	Price Group: SD				

Wing ermanently attached on the 1"

AD01

AD01

Couplings come with adaptor and wing nuts. These fittings have Male or Female NPT Threads and are designed to fit standard ground joint spuds, refer to page 181.

Boss[™] Wing Nut Caps



Boss™ Wing Nut & Caps							
Size (inch)	Size (mm)	Part No.	Price \$				
³∕₄ & 1	20 & 25	B12SC	85.00				
1¼ & 1½	32 & 40	B17SC	152.52				
2	50	B27SC	211.62				
3	75	B37SC	153.80				
Shown with Mal	Price Group: SD						

Boss™ Wing Nut caps are not intended for pressure applications

For best results, use with washer style spuds and washers.

Supplied with 12" chain and washer.

Boss[™] Holedall Fittings



ngs								
:	 designed for air and liquid applications where a permanent, low profile clamping system is desired not for steam service 							
	 supplied with carbon steel ferrules consult Dixon™ for swage and/or crimp specifications 							
Hose OD	Hose OD To (mm):	Plated Iron / Steel		Stainless Steel				
From (mm):		Part No.	Price \$	Part No.	Price \$			
29.36	30.95	GF26P1	149.33					
31.35	32.54	GF26P2	149.33					
32.94	34.13	GF26P3	149.33					
37.30	38.89	GF36P1	179.20					
39.29	39.68	GF36P2	179.20					
40.87	42.06	GF36P3	179.20					
33.33	50.80	GF61P1	378.32	RGF61P1	962.32			
51.19	53.97	GF61P2	378.32	RGF61P2	1070.05			
54.37	57.15	GF61P3	378.32					
65.08	66.67	GF81P1	348.44	RGF81P1	1093.25			
67.07	69.85	GF81P2	348.44	RGF81P2	1093.25			
70.24	73.02	GF81P3	348.44					
86.51	92.07	GF111P1 ¹	POR					
92.29	95.25	GF111P2 ¹	POR					
95.64	98.42	GF111P3 1	POR					
	Hose OD From (mm): 29.36 31.35 32.94 37.30 39.29 40.87 33.33 51.19 54.37 65.08 67.07 70.24 86.51 92.29	Hose OD From (mm): Hose OD To (mm): 29.36 30.95 31.35 32.54 32.94 34.13 37.30 38.89 39.29 39.68 40.87 42.06 33.33 50.80 51.19 53.97 54.37 57.15 65.08 66.67 67.07 69.85 70.24 73.02 86.51 92.07 92.29 95.25	system is desired • not for steam service • supplied with carbon steel ferrules • consult Dixon™ for swage and/or of Hose OD Plated Iron From (mm): To (mm): Plated Iron 29.36 30.95 GF26P1 31.35 32.54 GF26P2 32.94 34.13 GF26P3 37.30 38.89 GF36P1 39.29 39.68 GF36P2 40.87 42.06 GF36P3 33.33 50.80 GF61P1 51.19 53.97 GF61P2 54.37 57.15 GF81P1 67.07 69.85 GF81P2 70.24 73.02 GF81P3 86.51 92.07 GF111P1 ¹ 92.29 95.25 GF111P2 ¹	system is desired not for steam service • not for steam service • supplied with carbon steel ferrules • consult Dixon™ for swage and/or crimp specification Hose OD From (mm): Hose OD To (mm): Plated Iron / Steel 29.36 30.95 GF26P1 149.33 31.35 32.54 GF26P2 149.33 32.94 34.13 GF26P3 149.33 37.30 38.89 GF36P1 179.20 39.29 39.68 GF36P2 179.20 40.87 42.06 GF36P3 179.20 33.33 50.80 GF61P1 378.32 51.19 53.97 GF61P2 378.32 65.08 66.67 GF81P1 348.44 67.07 69.85 GF81P2 348.44 70.24 73.02 GF81P3 348.44 86.51 92.07 GF111P2 1 POR 92.29 95.25 GF111P2 1 POR	system is desired •			

¹ 3" have a machined shank

