

King Crimp™ Style Sleeves



Only use the crimp style shanks with the crimp style sleeves and ferrules.
Due to differences in dimensions and tolerances for safety reasons, DO NOT interchange other manufacturer's products with Dixon™ products.

D

Hose ID (inch)	Hose OD (mm)		Carbon Steel		304 Stainless Steel		WP (PSI)		Sleeve ID (mm)	Sleeve Wall Thickness (mm)	Sleeve Overall Length (mm)
	From	To	Part No.	Price \$	Part No.	Price \$	Cam & Groove ¹	KC Nipple ²			
3	81.36	82.55	CS300-1CS	25.19	CS300-1SS	25.19	125	200	84.15	2.29	95.0
3	82.95	84.14	CS300-2CS	25.19	CS300-2SS	25.19	125	200	85.73	2.29	95.0
3	84.53	85.73	CS300-3CS	25.19	CS300-3SS	25.19	125	200	87.33	2.29	95.0
3	86.12	87.31	CS300-4CS	25.19	CS300-4SS	25.19	125	200	88.90	2.29	95.0
3	89.30	90.49	CS300-6CS	25.19	CS300-6SS	25.19	125	200	92.08	2.29	95.0
3	90.88	92.08	CS300-7CS	25.19	CS300-7SS	25.19	125	200	93.68	2.29	95.0
3	92.47	93.66	CS300-8CS	25.19	CS300-8SS	25.19	125	200	95.25	2.29	95.0
3	94.06	95.25	CS300-9CS	25.19	CS300-9SS	25.19	125	200	96.85	2.29	95.0
3	95.65	96.84	CS300-10CS	25.19	CS300-10SS	25.19	125	200	98.43	2.29	95.0
3	97.23	98.43	CS300-11CS	25.19	CS300-11SS	25.19	125	200	100.03	2.29	95.0
3	98.82	100.01	CS300-12CS	25.19	CS300-12SS	25.19	125	200	101.60	2.29	95.0
3	100.41	101.60	CS300-13CS	25.19	CS300-13SS	25.19	125	200	103.20	2.29	95.0
3	102.00	103.19	CS300-14CS	25.19	CS300-14SS	25.19	125	200	104.78	2.29	95.0
3	103.58	104.78	CS300-15CS	25.19	CS300-15SS	25.19	125	200	106.38	2.29	95.0
3	105.17	106.36	CS300-16CS	25.19	CS300-16SS	25.19	125	200	107.95	2.29	95.0
4	106.76	107.95	CS400-1CS	40.30	CS400-1SS	30.23	110	175	109.55	2.29	95.0
4	108.35	109.54	CS400-2CS	40.30	CS400-2SS	30.23	110	175	111.13	2.29	95.0
4	109.93	111.13	CS400-3CS	30.23	CS400-3SS	30.23	110	175	112.73	2.29	95.0
4	111.52	112.71	CS400-4CS	30.23	CS400-4SS	30.23	110	175	114.30	2.29	95.0
4	113.11	114.30	CS400-5CS	30.23	CS400-5SS	30.23	110	175	115.90	2.29	95.0
4	114.70	115.89	CS400-6CS	30.23	CS400-6SS	30.23	110	175	117.48	2.29	95.0
4	116.28	117.48	CS400-7CS	30.23	CS400-7SS	30.23	110	175	119.08	2.29	95.0
4	117.87	119.06	CS400-8CS	30.23	CS400-8SS	30.23	110	175	120.65	2.29	95.0
4	119.46	120.65	CS400-9CS	40.30	CS400-9SS	30.23	110	175	122.25	2.29	95.0
4	121.05	122.24	CS400-10CS	40.30	CS400-10SS	30.23	110	175	123.80	2.29	95.0
4	122.63	123.83	CS400-11CS	40.30	CS400-11SS	30.23	110	175	125.43	2.29	95.0
4	124.22	125.41	CS400-12CS	40.30	CS400-12SS	30.23	110	175	127.00	2.29	95.0
4	125.81	127.00	CS400-13CS	40.30	CS400-13SS	30.23	110	175	128.60	2.29	95.0
4	127.40	128.59	CS400-14CS	40.30	CS400-14SS	30.23	110	175	130.18	2.29	95.0
4	128.98	130.18	CS400-15CS	40.30	CS400-15SS	30.23	110	175	131.78	2.29	95.0
4	130.57	131.76	CS400-16CS	40.30	CS400-16SS	30.23	110	175	133.35	2.29	95.0
6	157.56	163.51	CS600-1CS	72.54	CS600-1SS	90.68	*	*	165.10	3.05	140.0
6	163.91	163.91	CS600-2CS	72.54	CS600-2SS	90.68	*	*	168.28	3.05	140.0
6	167.08	169.86	CS600-3CS	72.54	CS600-3SS	90.68	*	*	171.45	3.05	140.0
6	170.26	173.04	CS600-4CS	72.54	CS600-4SS	136.01	*	*	174.63	3.05	140.0
6	173.43	176.21	CS600-5CS	72.54	CS600-5SS	90.68	*	*	177.80	3.05	140.0
6	176.61	179.39	CS600-6CS	72.54	CS600-6SS	90.68	*	*	180.98	3.05	140.0
6	179.78	182.56	CS600-7CS	72.54	CS600-7SS	90.68	*	*	184.15	3.05	140.0
6	182.96	185.74	CS600-8CS	72.54	CS600-8SS	90.68	*	*	187.33	3.05	140.0
6	186.13	188.91	CS600-9CS	72.54	CS600-9SS	90.68	*	*	190.50	3.05	140.0

* Consult Dixon™ for pressure rating.

¹ Based on using crimp cam & groove shanks

² Based on using King™ combination nipples

Price Group: SD

AU06



1300 134 651
dixonvalve.com.au

All prices exclude GST.
ADPL718