

External Ferrules

The selection of ferrules is very important to achieve the proper coupling-to-hose assembly. Style F ferrules are used with all standard length male stems. Ferrules are plated carbon steel.



F 1 1/4" - 5"
(2 holes)



F 6" - 10"
(6 holes)

Hose ID (mm)	Hose OD (mm)		Standard	
	From:	To:	Part No.	Price \$
32	42.9	44.5	F20-1	112.49
32	44.8	47.6	F20-2	112.49
32	48.0	50.8	F20-3	164.50
32	51.2	54.0	F20-4	25.30
40	48.4	50.8	F24-1	61.36
40	51.2	54.0	F24-2	61.36
40	54.4	57.2	F24-3	61.36
40	57.5	60.3	F24-4	61.36
50	61.9	66.7	F32-1	71.58
50	67.1	69.9	F32-2	71.58
50	70.2	73.0	F32-3	122.71
50	73.4	77.0	F32-4	122.71
65	77.4	79.4	F40-1	79.13
65	79.8	82.6	F40-2	146.24
65	82.9	85.7	F40-3	168.74
65	86.1	88.9	F40-4	153.39
65	89.3	92.1	F40-5	127.83
75	88.1	92.1	F48-1	117.40
75	92.5	95.3	F48-2	107.38
75	95.6	98.4	F48-3	122.71
75	98.8	101.6	F48-4	143.17
75	102.0	104.8	F48-5	156.53
100	113.5	117.1	F64-Z*	184.07
100	117.5	119.1	F64-1	189.19
100	119.5	122.2	F64-2	189.19
100	122.6	125.4	F64-3	201.50
100	125.8	128.6	F64-4	194.30
100	129.0	131.8	F64-5	235.20
100	132.2	134.9	F64-6	235.20
100	135.3	138.1	F64-7	235.20
100	138.5	141.3	F64-8	235.20
125	149.2	150.8	F80-1	194.30
125	151.2	154.0	F80-2	194.30
125	154.4	157.2	F80-3	276.11
125	157.6	160.3	F80-4	920.35
125	160.7	163.5	F80-5	296.56
125	163.9	166.7	F80-6	296.56
125	167.1	169.9	F80-7	296.56
150	169.9	177.4	F96-Z	296.56
150	177.8	179.4	F96-1	251.43
150	179.8	182.6	F96-2	263.46
150	183.0	185.7	F96-3	226.79
150	186.1	188.9	F96-4	276.11
150	189.3	192.1	F96-5	347.69
150	192.5	195.3	F96-6	347.69
150	195.7	198.4	F96-7	347.69
150	198.8	201.6	F96-8	224.97
150	202.0	203.2	F96-9	787.41
200	236.5	238.1	F128-1	937.64
200	238.5	241.3	F128-2	1026.35
200	241.7	244.5	F128-3	959.84
200	244.9	247.7	F128-4	784.02
200	248.0	250.8	F128-5	694.95
200	251.2	254.0	F128-6	715.98
200	254.4	255.6	F128-7	635.68



Dixon™ recommends using a diameter tape for determining correct ferrule size. Refer to page 593.

* Requires special stem Part # TM 64-42

Price Group: SD
AU03