

Dry Quick Disconnect Adaptor - Tank Unit

Application:	The adaptor is usually typically on the tank or manifold. Available in male and female BSP, NPT or 150# ASA flange (ANSI).
Design:	Conical valve seat to eliminate the risk for "piston blow out". PTFE bearing between the piston shaft and the piston guide to eliminate the risk for seizure.
Material:	Aluminium adaptor - aluminium poppet, stainless steel internal parts Stainless steel adaptor - stainless steel poppet, stainless steel internal parts Brass / gunmetal adaptor - brass poppet, brass and stainless steel internal parts Composite (Polyeten PE-HD 300) caps provide very good protection against corrosion and withstand hot and cold environments

Adaptors x Female NPT with FKM Seals

Female (inch)	Body Size (mm)	316 Stainless Steel		Anodised Aluminium		Brass / Gunmetal	
		Part No.	Price \$	Part No.	Price \$	Part No.	Price \$
NPT							
¾	56	DDA075SS	1504.45	DDA075AL	1077.85	DDA075BR	853.50
1	56	DDA100SS	1461.62	DDA100AL	754.27	DDA100BR	1099.81
1½	70	DDA150SS	1585.96	DDA150AL	660.08	DDA150BR	698.14
2	70	DDA200SS	1585.96	DDA200AL	660.08	DDA200BR	698.14
3	105	DDA300SS105	2191.58	DDA300AL105	2240.64	DDA300GM105	1070.75
3	119	DDA300SS	2077.13	DDA300AL	769.83	DDA300GM	1061.70
4	164	DDA400SS	3463.09	DDA400AL	1522.56	DDA400GM	2485.79
6	238	DDA600SS	14220.10	DDA600AL	7485.12	-	-
BSP							
¾	56	DDA075SSA	1504.45	DDA075ALA	1077.85	-	-
1	56	DDA100SSA	943.63	DDA100ALA	754.27	-	-
1½	70	DDA150SSA	1585.96	DDA150ALA	660.08	-	-
2	70	DDA200SSA	1530.33	DDA200ALA	798.24	-	-
3	105	DDA300SSA105	2176.20	DDA300ALA105	2191.15	-	-
3	119	DDA300SSA	1752.38	DDA300ALA	841.59	-	-
4	164	DDA400SSA	3691.82	DDA400ALA	1527.61	-	-
6	238	DDA600SSA	14220.10	DDA600ALA	7485.12	-	-

Adaptors x 150# ASA (ANSI) Flange with FKM Seals

150# Flange (inch)	Body Size (mm)	316 Stainless Steel		Anodised Aluminium		Brass / Gunmetal	
		Part No.	Price \$	Part No.	Price \$	Part No.	Price \$
¾	56	DDA075SSFL	2737.82	DDA075ALFL	1921.27	DDA075BRFL	2184.04
1	56	DDA100SSFL	2796.12	DDA100ALFL	1921.27	DDA100BRFL	2184.04
1½	70	DDA150SSFL	1903.64	DDA150ALFL	1741.13	DDA150BRFL	1358.60
2	70	DDA200SSFL	1903.64	DDA200ALFL	967.36	DDA200BRFL	1342.12
3	105	DDA300SS105FL	2633.66	DDA300AL105FL	2244.93	DDA300GM105FL	2244.93
3	119	DDA300SSFL	2613.14	DDA300ALFL	1321.67	DDA300GMFL	1632.73
4	164	DDA400SSFL	4512.53	DDA400ALFL	1825.45	DDA400GMFL	3060.48
6	238	DDA600SSFL	21782.27	DDA600ALFL	7953.58	-	-

Adaptors x TTMA Flange with FKM Seals

TTMA Flange (inch)	Body Size (mm)	Anodised Aluminium	
		Part No.	Price \$
3	105	DDA300AL105TTMA	1614.29
3	119	DDA300AL119TTMA	1804.42
4	164	DDA400AL164TTMA	2613.77

Price Group: SD
AS01

Dust Caps for Adaptors



Composite Dust Cap

Size (inch)	Body Size (mm)	Polyeten PE-HD 300	
		Part No.	Price \$
¾ & 1	56	DDDC075	453.55
1½ & 2	70	DDDC150	246.68
3	105	DDDC300105	306.52
3	119	DDDC300	324.05
4	164	DDDC400	497.76
6	238	DDDC600 *	2362.11

* 6" dust plug is aluminium.

Price Group: SD
AS01

