

A Rubber Extra High Pressure Hot Water Wash Hose (PW206)




Application:	Used for high pressure hot water cleaning applications.
Tube:	Hot water and detergent solutions resistant, special synthetic rubber.
Reinforcement:	2 wire braids
Cover:	Blue, oil, abrasion and weather resistant non-marking synthetic rubber
Temperature:	-40°C to 150°C
Special Features:	<ul style="list-style-type: none"> • Weather resistant, ozone resistant. • Minimum cut length of 10 mtrs, charges apply for cutting hose.

Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Coil Lengths	Price \$ per mtr
	ID	OD	PSI	MPa					
PW206	9.5	18	5800	40	29000	130	0.53	Random	24.24

Price Group: HR

DC04

Rubber Hot Water Washdown (A225)



Application:	Used for cleaning food processing equipment in meat, poultry, confectionery and dairy plants.
Tube:	NBR white
Reinforcement:	4 spiral polyester
Cover:	NBR white
Temperature:	-20°C to 90°C
Special Features:	<ul style="list-style-type: none"> • Oil mist resistant • Minimum cut length of 10 mtrs, charges apply for cutting hose.

Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Coil Lengths	Price \$ per mtr
	ID	OD	PSI	MPa					
A225012	12.5	21.9	300	2	900	75	0.39	2 x 100M	11.85
A225020	19	30.2	300	2	900	114	0.7	2 x 100M	18.94
A225025	25	38.0	300	2	900	150	1.2	2 x 100M	29.35

Price Group: HR

DB29

Complete hose data specification sheets are available upon request.