

Ball Valves (Encapsulated)

Application:	Hygienic Ball valves for food and chemical use with ISO mount plate 1000 PSI WOG.
End Connection:	Weld, SMS, DIN, RJT, Triclover, ends available.
Options:	Repair Kits available, direct mount actuation, double air to spring and electric.
Standards:	RJT, SMS, DIN, Triclover and IDF, CF8M 316 SS
Seal Options:	Std PTFE, RTFE, 25% Carbon PTFE, SS Reinforced PTFE, UHMW (please specify when ordering)



Hygienic Ball Valve				
Size (inch)	Weld Ends		Clamp Ends	
	Part No.	Price \$	Part No.	Price \$
½	BV2CV-050BB-A	209.75	BV2CV-050CC-A	209.75
¾	BV2CV-075BB-A	242.97	BV2CV-075CC-A	242.97
1	BV2CV-100BB-A	322.63	BV2CV-100CC-A	322.63
1½	BV2CV-150BB-A	557.53	BV2CV-150CC-A	557.53
2	BV2CV-200BB-A	815.89	BV2CV-200CC-A	815.89
2½	BV2CV-250BB-A	1887.16	BV2CV-250CC-A	1887.16
3	BV2CV-300BB-A	2243.29	BV2CV-300CC-A	2243.29
4	BV2CV-400BB-A	3846.71	BV2CV-400CC-A	3846.71

Price Group: DS

VS03

BV3/4 Series Multi-port Sanitary Stainless Steel Ball Valves

Sizes:	<ul style="list-style-type: none"> • ½" thru 4"
Materials:	<ul style="list-style-type: none"> • body, ends and ball: CF8M stainless • seats: virgin PTFE, 15% glass reinforced RTFE, 25% carbon reinforced PTFE, 50% stainless steel reinforced PTFE or UHMW
Features:	<ul style="list-style-type: none"> • full port design on ½" thru 3" • reduced port design on 4" • blow-out proof stem • live-loaded stem packing • ISO 5211 mounting pad • lock-out, tag out
Specifications:	<ul style="list-style-type: none"> • maximum pressure rating: ½" - 2" 1000 PSI WOG, 2½" - 4" 800 PSI WOG



Size (inch)	Weld Ends		Clamp Ends	
	Part No.	Price \$	Part No.	Price \$
½	BV3SVTF050C-A	904.32	BV3SVLF050C-A	923.97
¾	BV3SVTF075C-A	1085.97	BV3SVLF075C-A	1105.20
1	BV3SVTF100C-A	1431.36	BV3SVLF100C-A	1476.71
1½	BV3SVTF150C-A	2419.51	BV3SVLF150C-A	2518.66
2	BV3SVTF200C-A	3636.41	BV3SVLF200C-A	3801.70
2½	BV3SVTF250C-A	6091.20	BV3SVLF250C-A	6279.53
3	BV3SVTF300C-A	8602.15	BV3SVLF300C-A	8846.95
4	BV3SVTR400C-A	12577.15	BV3SVLR400C-A	12617.90

Price Group: DS

VS03