

Shouldered Gate Valves Fig GVNR-S-1161

Design:	Non-rising stem Gate Valve. Shoulder dimensions are made in accordance with metric pipe.
End Connection:	Shouldered
Body Materials:	Ductile iron body, Stainless steel stem, bronze seat
Wedge:	Cast iron wedge
Approvals:	Conforms to BS5150 - PN20 rated
Application:	Water and slurry applications - mining

Face to Face Dim	Part No.	Size NB (mm)	Price \$
229	GVNR-S-1161-100	100	819.85
267	GVNR-S-1161-150	150	1639.71

Price Group: SD
VC05



Monitored Gate Valves Table E, Ductile Iron Flanged Fig F0111-200

Design:	OS&Y Gate Valve
End Connection:	Flanged, Table D/E, AS2129
Body Materials:	Ductile Iron, ASTM A126 Class B
Wedge:	EPDM encapsulated wedge, Resilient seated
Temperature:	Pressure temperature rating 1400/ 1600kPa @ 0.6°C to 52°C
Approvals:	UL/FM approved
Application:	For water, sewerage & neutral liquids. Bubble tight shut off. Suitable for fire protection and distribution services. Valves with supervisory switches are required eg fire distribution services.
Mon Devices:	Class B - Potter - UL / FM - Standard
Options:	Australian standard, Switch

Face to Face Dim	Part No.	Size NB (mm)	Price \$
229	VG172-OSYE100ATS	100	1564.62
267	VG172-OSYE150ATS	150	2079.71
292	VG172-OSYE200ATS	200	3398.22
330	VG172-OSYE250ATS	250	4793.27
356	VG172-OSYE300ATS	300	6810.76

Note: Supplied in kit form for assembly at site.

Price Group: SD
VC04



Gate Valves Fig GVRC-1161

Design:	OS&Y Gate Valve
End Connection:	Flanged, AS2129 Table D/E
Body Materials:	Cast iron body with wedge, bronze seat
Temperature:	Pressure temperature rating 1600kPa at -10 to 120°C.
Approvals:	Conforms to BS5150, MSS SP-70. Flange conforms to BS 4504 PN 16, ANSI 125 and drilled to Table E.
Application:	Water, oil & gas

Face to Face Dim	Part No.	Size NB (mm)	Price \$
190	GVRC1161-065	65	670.94
203	GVRC1161-080	80	944.35
229	GVRC1161-100E	100	690.26
229	GVRC1161-100D	100	690.26
267	GVRC1161-150	150	1261.55
292	GVRC1161-200	200	2131.63
330	GVRC1161-250	250	4760.68
356	GVRC1161-300	300	3770.41

Note: Sizes 350-600 available on request.

Price Group: SD
VC05

