

Bronze Swing Check Valves

Design:	Can be used in either vertical or horizontal pipelines.
End Connection:	Screwed female BSP
Body Material:	Bronze
Temperature:	Max 99°C
Pressure:	Max 2000 kPa Water, Oil & Gas
Application:	General hydraulic, mechanical services and Fire Protection

Part No.	Size (mm)	Price \$
VC-4B-015	15	93.61
VC-4B-020	20	86.50
VC-4B-025	25	125.72
VC-4B-032	32	233.81
VC-4B-040	40	335.43
VC-4B-050	50	398.57
VC-4B-080	80	925.21
VC-4B-100	100	1668.41

Price Group: SD
VB11



Australian
Standard
AS1628



Brass Swing Check Valves

Design:	General Purpose
End Connection:	Screwed female BSP. DIN259 and BS2779
Body Material:	Brass
Application:	For control of water, oil and gas in hose or pipe lines, irrigation, light industrial and rural applications. For other services, please contact Dixon™.

Size (mm)	Part No.	Working Pressure		Price \$
		PSI	MPa	
15	BSCV012	170	1.2	19.53
20	BSCV020	170	1.2	27.13
25	BSCV025	170	1.2	40.53
32	BSCV032	140	1	58.95
40	BSCV040	140	1	76.93
50	BSCV050	140	1	109.03
65	BSCV065	110	0.8	240.07
80	BSCV075	110	0.8	326.63
100	BSCV100	110	0.8	540.34

Price Group: SD
VB02



Stainless Steel Swing Check Valves

End Connection:	Screwed female BSP
Body Material:	316 Stainless steel
Pressure:	200 PSI
Temperature:	-20 to 232°C for water, oil & gas & corrosive fluids

Size NB (mm)	Part No.	Price \$
15	SSC-015	64.68
20	SSC-020	80.85
25	SSC-025	118.58
32	SSC-032	167.08
40	SSC-040	199.42
50	SSC-050	280.27

Price Group: SD
VS01

